

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan


“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 9235 (1979, Reaffirmed 2009): Method for Physical Analysis and Determination of Moisture in Solid Wastes (Excluding Industrial Solid Wastes). UDC 628.4 :543.812



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam


“Knowledge is such a treasure which cannot be stolen”

(Reaffirmed 2009)

IS : 9235 - 1979

Indian Standard
METHOD FOR
PHYSICAL ANALYSIS AND DETERMINATION
OF MOISTURE IN SOLID WASTES
(EXCLUDING INDUSTRIAL SOLID WASTES)

UDC 628.1 : 543.812



© Copyright 1979

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

December 1979

**AMENDMENT NO. 1 SEPTEMBER 2005
TO
IS 9235:1979 METHOD FOR PHYSICAL
ANALYSIS AND DETERMINATION OF MOISTURE IN
SOLID WASTES (EXCLUDING INDUSTRIAL SOLID
WASTES)**

(First cover page, pages 1 and 3, title) — Substitute title of the standard as follows in the cover page and wherever it appears

**'METHOD FOR DETERMINATION OF MOISTURE IN
SOLID WASTES (EXCLUDING INDUSTRIAL WASTES)'**

(CHD 32)

Reprography Unit, BIS, New Delhi, India

Indian Standard

METHOD FOR PHYSICAL ANALYSIS AND DETERMINATION OF MOISTURE IN SOLID WASTES (EXCLUDING INDUSTRIAL SOLID WASTES)

Solid Wastes Sectional Committee, CDC 54

<i>Members</i>	<i>Representing</i>
ADVISER (PRE)	Ministry of Works & Housing, New Delhi
SHRI M. ANAND	Indian Sugar Mills Association, Calcutta
SHRI S. C. ANAND	Rajasthan State Agro Industries Corporation Ltd, Jaipur
SHRI Y. K. LUMB (Alternate)	
SHRI F. A. ATTARWALA	Municipal Corporation of Greater Bombay
SHRI V. B. SHIRODKAR (Alternate)	
SHRI P. K. BANERJEE	The Corporation of Calcutta, Calcutta
SHRI B. B. BHALLERAO	Engineers India Ltd, New Delhi
SHRI A. D. JALGAONKAR (Alternate)	
SHRI R. K. BHAVE	Steel Authority of India Ltd, Rourkela Steel Plant, Rourkela
SHRI T. A. SUBRAMANIAN (Alternate)	
SHRI P. L. BURMAN	Indian Paper Mills Association, Calcutta
SHRI T. G. CHANDARAN	Kaira District Co-operative Milk Processors Union Ltd, Anand
DR H. C. GUPTA (Alternate)	
SHRI A. H. GANDHI	Municipal Corporation, Ahmadabad
SHRI J. D. GOEL	Municipal Corporation of Delhi
SHRI JWALA PRASAD	Ministry of Agriculture & Irrigation (Animal Husbandry Division), New Delhi
SHRI J. N. MUKHERJEE	Steel Authority of India Ltd, Durgapur Steel Plant, Durgapur
SHRI H. C. NANDI	Central Fuel Research Institute (CSIR), Dhanbad
SHRI A. RAMA RAO	Khadi & Village Industries Commission, Bombay
SHRI S. SUBBA RAO	All India Institute of Hygiene and Public Health, Calcutta
SHRI A. V. RAO (Alternate)	
SHRI B. V. ROTKAR	Maharashtra Prevention of Water Pollution Board, Bombay
SHRI A. G. PANDIT (Alternate)	

(Continued on page 2)

© Copyright 1979

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act

IS : 9235 - 1979

(Continued from page 1)

Members	Representing
DR A. ROY	Indian Jute Industries Research Association, Calcutta
SHRI P. K. SAHA	Calcutta Metropolitan Development Authority, Calcutta
SHRI DALJIT SINGH	Steel Authority of India Ltd, Bhilai Steel Plant, Bhilai
SHRI J. C. SEHGAL (Alternate)	
DR S. K. SINHA	The Tata Iron and Steel Co Ltd, Jamshedpur
SHRI C. S. SRIDHARAN	Indian Council of Agricultural Research, New Delhi
DR B. B. SUNDARESAN	National Environmental Engineering Research Institute (CSIR), Nagpur
SHRI A. D. BHIDE (Alternate)	
SHRI S. VENKATARAMAN	King Institute, Madras
DR G. M. SAXENA, Director (Chem)	Director General, ISI (Ex-officio Member)

Secretary

SHRI A. K. BARI
Assistant Director (Chem), ISI

Panel for Methods of Sampling and Test for Solid Wastes,
CDC 54 : P4

SHRI J. C. PAUL	Steel Authority of India Ltd, Bhilai Steel Plant, Bhilai
DR A. V. S. PRABHAKARA RAO	Indian Institute of Technology, Kanpur
SHRI S. C. SHARMA	Indian Sugar Mills Association, Calcutta
SHRI C. S. SRIDHARAN	Indian Council of Agricultural Research, New Delhi
DR D. C. TAPADAR	Indian Paper Mills Association, Calcutta
SHRI A. SATYANARAYANA (Alternate)	
SHRI V. P. THERGAONKAR	National Environmental Engineering Research Institute (CSIR), Nagpur
SHRI S. K. TITUS (Alternate)	
SHRI S. VENKATARAMAN	King Institute, Madras

Indian Standard
**METHOD FOR
PHYSICAL ANALYSIS AND DETERMINATION
OF MOISTURE IN SOLID WASTES
(EXCLUDING INDUSTRIAL SOLID WASTES)**

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 16 July 1979, after the draft finalized by the Solid Wastes Sectional Committee had been approved by the Chemical Division Council.

0.2 The term 'solid waste' as used in this standard includes raw refuse (domestic, shop, office, institutional and street) delivered to a processing facility, or in various stages of composting. It also includes residues of the incineration process.

0.3 In the preparation of this standard, considerable assistance has been derived from the publication 'Methods of sampling and analysis of solid wastes. Section for solid waste, EAWAG, CH 8600 Dubendorf (Switzerland) issued by the Swiss Federal Institute for Water Supply, Sewage Purification and Water Pollution Control.

0.4 In reporting the result of a test or analysis, made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS : 2-1960*.

1. SCOPE

1.1 This standard prescribes a method for physical analysis and determination of moisture in solid wastes excluding industrial wastes.

2. GENERAL REQUIREMENTS OF SAMPLING

2.0 It is of utmost importance for all analyses that the samples be representative. Cursory samplings reveal very little about the true composition of the material and may lead to erroneous conclusions.

*Rules for rounding off numerical values (*revised*).

IS : 9235 - 1979

2.1 Refuse

2.1.1 A mobile hammermill shall be used to take a crude sample of refuse so that the refuse to be examined may be ground and homogenized on the spot.

2.1.2 Crude refuse 100 to 200 kg may be taken as the basic unit for a sample which may be taken at variable intervals depending on the amount of waste. In accordance with the purpose of the analysis, 2 to 4 individual samples may be ground together in order to reduce the number of samples during more lengthy tests.

2.1.3 The ground refuse has to be mixed intensively. During mixing, about 10 to 20 small individual portions are taken and filled into air-tight plastic bags in quantities of 1 to 2 kg, to be stored as samples. This heterogeneous mixture is the *crude sample*.

2.2 Compost — Grab samples (1 to 2 kg) shall be taken from as many parts of the windrow as possible and well mixed. It shall be ensured that equal amounts are taken from all parts. The actual sample of 1 to 2 kg shall be taken from this mixture. In the same way compost samples shall be taken from the test material in plastic baskets and small windrows. The mixture obtained in this way is the *crude sample*.

2.3 Sewage Sludge — Before a sample is taken, the sewage sludge shall be well homogenized. However, too intensive mixing with a high speed agitator should be avoided if the sample is to be used in dehydration tests (flocculation and filtration tests) . The sewage sludge obtained in this way is the *crude sample*.

2.4 Residue After Incineration

2.4.1 The crude sample shall be taken directly from the conveying system under examination if possible. Fly ash and riddlings shall be taken from the corresponding areas.

2.4.2 The size of the sample shall depend on the kind of information sought and the structure of the material. In the case of single samplings (which may have a random composition), a large quantity should be taken and prepared. For longer examination periods, in which several single samples are taken at smaller intervals, the quantity may be fixed at 100 kg per sampling. Considerable deviations may occur with smaller quantities.

2.4.3 Depending on the information sought, 2 to 4 single samplings may be ground and mixed in order to limit the number of samplings for lengthier tests.

3. PREPARATION OF SAMPLES

3.1 Crude samples are not ready for examination. They should be ground and homogenized further after drying. The moisture content of the crude sample is determined during drying. It is essential that this moisture content of sample is measured as soon as possible after the sample is collected.

NOTE — If any moisture is found condensed on the walls of the container, it should be reabsorbed in the sample.

4. DETERMINATION OF MOISTURE

4.1 Procedure — In order to determine the moisture content, weigh the entire *crude sample*. Spread it thinly and dry in a drying oven till its mass becomes constant. Drying may be generally done at 105°C but in case of combustibles the temperature shall be 70 to 75°C. However, if microbiological tests are also to be conducted, drying shall be done at 40 to 50°C. The dried crude samples are somewhat hygroscopic. They shall be left to cool in a turned off drying oven and weighed immediately afterwards.

4.2 Calculation

$$DS + W = 100 (NS)$$

$$c = a - b$$

$$e = d - b$$

$$W = \frac{c - e}{c} \times 100$$

$$DS = \frac{e}{c} \times 100$$

where

DS = dry substance of the *crude sample*, percent by mass;

W = moisture content of the *crude sample*, percent by mass;

NS = non-dried substance of the *crude sample*;

c = net mass, wet;

a = gross mass, wet;

b = mass of receptacle (tare);

d = gross mass, dried; and

e = net mass, dried.

5. SEGREGATION AND GRINDING

5.1 Waste material may contain glass, ferrous and non-ferrous metals, plastics, etc. Glass and ceramics may be separated by judicious sieving, plastics and non-ferrous metals may be hand-picked and ferrous metals may be removed by a strong magnet.

5.2 The remaining material may be ground with an appropriate pulverizing equipment (crushing mill, hammermill, ball mill, knife mill) until it becomes a farinaceous, homogeneous powder which is sifted through a 0.5 mm screen. The screening residue should be ground thoroughly to particles of the smallest size possible. The material in the form of sample is now ready for analysis.

5.3 The separated material may further be segregated into organic and inorganic portion. The organic portion consists mainly of paper, rubber, plastics, wood, textiles and cork. A part of these materials may be pulverized even further with a knife mill and mixed with the sample. This is of importance if it is desired to determine the carbon content of fermentable organic substance and volatile substance. The mass of the remaining material shall be determined and expressed as a percentage of the dry substance and referred to as the organic screening residue.

5.4 The inorganic screening residue consists almost exclusively of metals. They shall be cleaned with air pressure and their mass determined and expressed as a percentage of the dry substance.

5.5 The screening residue should be taken into account when calculating the results of analysis of the *crude sample*. The inorganic screening residue shall be considered inert while calculating the calorific value. An approximate value shall be used for the organic part, if necessary.

6. RESULTS OF ANALYSIS

6.0 The moisture content of the *crude sample* is closely linked with the place and method by which it was taken and whether it was immediately mixed and filled into containers or only after some time.

6.1 To facilitate comparison of results, the data of analysis shall be normally calculated on the basis of dry substance.

6.2 When a single crude sample is drawn and analysed in order to obtain information about the quantity of a sample unaffected by a process or to determine its state, it shall be referred to as *single analysis*.

6.3 When crude samples are taken and analyzed at various intervals depending upon purpose and process, it shall be referred to as *series analysis*.

6.4 Single Analyses — These shall be calculated as given below.

6.4.1 Evaluation shall be done on the basis of dry substance (DS) in percentage by mass.

6.4.2 Evaluation shall be done on the basis of the non-dry substance (NDS) also in percentage by mass.

6.5 Series Analyses — These shall be calculated as given below.

6.5.1 Evaluation shall be done on the basis of initial dry substance (IDS) in percentage by mass.

6.5.2 The results of analysis of a series of tests carried out to follow fermentation shall be calculated on the basis of the following assumptions:

- a) The ash content remains constant during fermentation from the quantitative point of view. The organic part, however, decomposes and hence there is a quantitative reduction.
- b) All results may be converted and compared with each other with the aid of sample's ash content as well as IDS of the sample.

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

QUANTITY	UNIT	SYMBOL
Length	metre	m
Mass	kilogram	kg
Time	second	s
Electric current	ampere	A
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol

Supplementary Units

QUANTITY	UNIT	SYMBOL
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

QUANTITY	UNIT	SYMBOL	DEFINITION
Force	newton	N	$1 \text{ N} = 1 \text{ kg.m/s}^2$
Energy	joule	J	$1 \text{ J} = 1 \text{ N.m}$
Power	watt	W	$1 \text{ W} = 1 \text{ J/s}$
Flux	weber	Wb	$1 \text{ Wb} = 1 \text{ V.s}$
Flux density	tesla	T	$1 \text{ T} = 1 \text{ Wb/m}^2$
Frequency	hertz	Hz	$1 \text{ Hz} = 1 \text{ c/s (s}^{-1}\text{)}$
Electric conductance	siemens	S	$1 \text{ S} = 1 \text{ A/V}$
Electromotive force	volt	V	$1 \text{ V} = 1 \text{ W/A}$
Pressure, stress	pascal	Pa	$1 \text{ Pa} = 1 \text{ N/m}^2$

PUBLICATIONS OF INDIAN STANDARDS INSTITUTION INDIAN STANDARDS

Over 9 500 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Chemical Group fall under the following categories:

Acids	Linters and allied products
Adhesives	Lubricants and related products
Alcohols and allied products	Oil pastes
Alkalies	Oils and fats, oleaginous seeds and fruits
Brushware	Painters' materials (miscellaneous)
Ceramicware, enamelware and laboratory porcelain	Paper and its products
Chemical hazards and safety	Paper and pulp board packaging materials
Chemicals, inorganic (miscellaneous)	Perfumery materials, natural and synthetic
Chemicals, organic (miscellaneous)	Petroleum and petroleum products
Coal and coke	Photographic chemicals
Coal carbonization products	Pigments and extenders
Coated fabrics	Plastics
Cosmetics and toilet goods	Polishes
Dental materials	Printing inks
Drying oils	Ready mixed paints and enamels
Dye intermediates	Rubber and rubber products
Electroplating chemicals	Soaps and other surface active agents
Explosive and pyrotechnic materials	Tanning materials and allied products
Fertilizers	Thermal insulation materials
Filters, stoppers and putties	Thinners and solvents
Footwear	Varnishes and lacquers
Glass and glassware	Water and water treatment
Industrial gases	Water based paints
Inks and allied products	Unclassified
Laboratory glassware, thermometers and related apparatus	
Lac and lac products	
Leather, leather goods and leather dressings	

OTHER PUBLICATIONS

ISI Bulletin (Published Every Month)			
Single Copy	...	...	Rs 4.00
Annual Subscription	...	...	Rs 36.00
Standards - Monthly Additions			
Single Copy	...	...	Rs 0.30
Annual Subscription	...	...	Rs 3.00
Annual Reports (from 1248-49 Onwards)	...	...	Rs 2.00 to 7.00
ISI Handbook 1978	...	...	Rs 60.00

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones : 26 60 21, 27 81 31

Telegrams : Manaksanstha

Regional Offices :

		Telephone
Western : Novelty Chambers, Grant Road	BOMBAY 400007	37 97 29
Eastern : 5 Chowringhee Approach	CALCUTTA 700072	23-08 02
Southern : C.I.T. Campus Adyar	MADRAS 600020	41 24 42

Branch Offices :

'Pushpak' Nurmohamed Shaikh Marg, Khanpur	AHMADABAD 380001	2 03 91
'F' Block, Unity Bldg, Naresimharaja Square	BANGALORE 560002	2 76 49
Gangotri Complex, Bhadbhada Road, T.T. Nagar	BHOPAL 462003	6 27 16
22E Kalpane Area	BHUBANESHWAR 751014	5 36 27
Ahimsa Bldg, SCO 82-83, Sector 17C	CHANDIGARH 160017	2 83 20
6-8-56C L.N. Gupta Marg	HYDERABAD 500001	22 10 83
D-277 Todarmal Marg, Banipark	JAIPUR 302006	6 98 32
117/418 B Sarvodaya Nagar	KANPUR 208005	8 12 72
Pailiputra Industrial Estate	PATNA 800013	6 28 08
Hantex Bldg (2nd Floor), Rly Station Road	TRIVANDRUM 695001	32 27

Printed at Printograph, New Delhi, India